
Cleanroom Gowning/Degowning Procedure

PROCEDURE

M-CC-P-004 REVISION A

Prerequisites:

Clean, non-frayed work clothes (no sweaters, no torn clothes, nothing soiled, no tank tops), clean and dry closed toe shoes, no perfume or makeup. Training is to be current.

Gowning Procedure

1.	Upon entering the anteroom one must walk on the tacky mats to remove any possible contamination on the sole of their shoes.
2.	Immediately after entering the anteroom put on a pair of disposable shoe covers, bouffant (tuck all hair inside, and cover ears with bouffant), and gloves.
3.	Move to the clean side of the room.
4.	Obtain the correct size hood, suit, and boots required for gowning.
5.	Place head cover on head, completely covering bouffant hair cover, by handling only the inside of hood. Adjust snaps or ties for a snug fit and proper face/neck seal.
6.	Place facemask on.
7.	Place the one-piece coverall on, being careful not to allow the coverall to drag on the floor. Tuck the head cover bibs completely inside the coverall and zip the coverall up completely.
8.	Snug up slack material around the ankle and snap the leg of the coverall closed with pant leg completely inside the garment.
9.	Place clean room full length boots on and tuck the coverall into the boots. Make sure the gaiter is snapped to the coverall behind the calf and the boots are snapped tight around the leg.
10.	Put hardhat or communicator on as needed at this time.

11.	Inspect completed gown in mirror, fix any loose hair and ensure minimal skin is exposed.
12.	Upon entering the cleanroom area be sure to walk on the tack mat. If tacky mat appears visibly contaminated or are no longer tacky replace the mat.
	End of Procedure

Degowning Procedure

1.	Upon leaving the cleanroom area degown on the clean side by removing boots, coverall, then facemask and hood in that order.
2.	Place garments in correct laundry baskets or hang for subsequent use. Laundry baskets are segregated by boots and coveralls. Do not place garments in the wrong baskets as boots typically have more contamination than coveralls.
3.	Move to the street cloths side and remove bouffant, shoe covers and gloves.
4.	Exit the anteroom.
	End Of Procedure

M-CC-P-004 Cleanroom Gowning/Degowning Procedures

Document Release:

Approval for release of this document into the PDM system was granted by:

Keith Thorp	LLE Facility Manager
Samuel F. B. Morse	OMEGA EP Project Manager
James L. Edwards	OMEGA EP System Engineer
Dino Mastrosimone	OMEGA EP Integration Manager
Brian Ashe	OMEGA EP Contamination Control Engineer
Milton Shoup	OMEGA EP Chief Mechanical Engineer