

Characterizing Debris-Shield Transmission Degradation and Estimating On-Target Energy



J. KWIATKOWSKI, S. J. STAGNITTO, S. F. B. MORSE, M. LABUZETA, and V. GUILIANO

University of Rochester, Laboratory for Laser Energetics

Summary


OMEGA now provides an estimate of on-target transmission losses resulting from target debris contamination of blast window assemblies

- Transmission of OMEGA debris shields is highly dependent on the type of experimental campaigns
- A laser-cleaning effect generally maintains individual beam transmission to ~90% of the "clean" blast-window-assembly (BWA) condition
- Blowthrough Omega Transport Imaging System (OTIS) measurements are used to monitor debris-shield transmission throughout the BWA cycle
- An energy report is now provided to the Principal Investigators (PI's) depicting estimated UV transmission losses
- Experiments with low debris impact are generally scheduled at the start of a BWA cycle, and high-impact shots precede refurbishment

Debris shields will be changed ~15x in FY12.

09402a

Target debris collects on the surface of the debris shield and reduces the UV on-target energy





- The BWA consists of a vacuum window and a debris shield
- Surface contamination often exceeds 10^6 dpm²/100 cm²
- Processing of BWA's is labor intensive and requires
 - controlled surface contamination areas (CSCA)
 - qualified radiation workers
 - hardware decontamination
 - recoating or replacing debris shield

*dpm: disintegrations per minute

09403a


A "laser-cleaning effect" is observed after shooting the beam through a low-transmission debris shield

- High-loss beams generally recover up to ~90% of "clean" transmission after the beam is fired
- A majority of the laser-cleaning effect is realized after a single shot



09409


Blowthrough OTIS of two witness beam pairs is used to estimate individual transmission of all 60 beams



- Historical correlation of witness beam-pair blowthrough transmission is used to determine the overall system average
- Individual beam transmissions are calculated based on each beam's historical correlation to the system average
- Blowthrough OTIS predicts
 - 60-beam average transmission to ~1%
 - individual beam transmission for beams that are shot to <2% rms*

09406

UV on-target energy is calculated based on an energy measurement made upstream of the target chamber




- A harmonic-energy detector (HED) measures on-shot UV along with residual IR and green
- HED is calibrated semi-annually (seven shots) and checked monthly (one shot) against a conventional calorimeter



09404


"Mid-cycle" OTIS measurements of all 60 beams are now taken to understand debris-shield transport degradation after two weeks of target shots



- Overall system, as well as beam-to-beam, transmission can vary widely
- Historical HED report specifies UV on-target energy based on clean debris-shield transmission


09405a

Several factors contribute to the magnitude and distribution of debris-shield transmission degradation




09407a

Examples of blowthrough-estimated individual beam losses compared to actual OTIS measurements




09407

OTIS is used to measure absolute UV transmission of all 60 Individual beams when new BWA's are installed (~monthly)




09405b

UV transmission throughout each BWA cycle is highly campaign dependent



09408

Daily "blowthrough OTIS" measurements are used to monitor debris-shield transmission degradation in a subset of beams



09410a

Operations now provides an HED report that estimates UV on-target energy as a function of beamline

Beam	UV Energy	Estimate	DPP	Estimated DPP	Adj. On-Target Transmission	UV Energy
11	852.6	-0.6%	355	92.0%	92.0%	852.6
13	474.6	-0.5%	355	92.0%	92.0%	474.6
14	305.7	-0.6%	355	92.0%	92.0%	305.7
15	469.9	-0.6%	355	92.0%	92.0%	469.9
24	452.7	-0.6%	355	92.0%	92.0%	452.7
32	452.6	-0.5%	355	92.0%	92.0%	452.6
47	471.7	-0.6%	355	92.0%	92.0%	471.7
59	474.6	-0.5%	355	92.0%	92.0%	474.6
66	471.7	-0.6%	355	92.0%	92.0%	471.7
67	462.6	-0.6%	355	92.0%	92.0%	462.6
68	457.5	-0.6%	355	92.0%	92.0%	457.5
69	494.3	-0.6%	355	92.0%	92.0%	494.3
Sheet	452.9	-0.5%	355	92.0%	92.0%	452.9
SDCN	2.0	-0.2%	355	92.0%	92.0%	2.0
0/7%	1.0	1.0%	355	92.0%	92.0%	1.0

- Estimated DPP transmission is included in this report
 - SG4 DPP transmission is beam specific
 - non-SG4 DPP's are not beam specific; quoted transmission are the average for that DPP type
- This report is included in
 - PI Packet
 - Shot Images and Reports page
 - OMEGA Data Viewer

09409

Summary


OMEGA now provides an estimate of on-target transmission losses resulting from target debris contamination of blast window assemblies



- Transmission of OMEGA debris shields is highly dependent on the type of experimental campaigns
- A laser-cleaning effect generally maintains individual beam transmission to ~90% of the “clean” blast-window-assembly (BWA) condition
- Blowthrough Omega Transport Imaging System (OTIS) measurements are used to monitor debris-shield transmission throughout the BWA cycle
- An energy report is now provided to the Principal Investigators (PI's) depicting estimated UV transmission losses
- **Experiments with low debris impact are generally scheduled at the start of a BWA cycle, and high-impact shots precede refurbishment**

Debris shields will be changed ~15× in FY12.


UV on-target energy is calculated based on an energy measurement made upstream of the target chamber




- A harmonic-energy detector (HED) measures on-shot UV along with residual IR and green
- HED is calibrated semi-annually (seven shots) and checked monthly (one shot) against a conventional calorimeter



OTIS is used to measure absolute UV transmission of all 60 Individual beams when new BWA's are installed (~monthly)




Target debris collects on the surface of the debris shield and reduces the UV on-target energy




- The BWA consists of a vacuum window and a debris shield
- Surface contamination often exceeds 10^6 dpm*/100 cm²
- Processing of BWA's is labor intensive and requires
 - controlled surface contamination areas (CSCA)
 - qualified radiation workers
 - hardware decontamination
 - recoating or replacing debris shield

“Mid-cycle” OTIS measurements of all 60 beams are now taken to understand debris-shield transport degradation after two weeks of target shots




- Overall system, as well as beam-to-beam, transmission can vary widely
- Historical HED report specifies UV on-target energy based on clean debris-shield transmission

UV transmission throughout each BWA cycle is highly campaign dependent





A “laser-cleaning effect” is observed after shooting the beam through a low-transmission debris shield

- High-loss beams generally recover up to ~90% of “clean” transmission after the beam is fired
- A majority of the laser-cleaning effect is realized after a single shot




Beams with transmission loss >5% over the last ten mid-cycle OTIS runs



Several factors contribute to the magnitude and distribution of debris-shield transmission degradation

Average UV transport losses measured on mid-cycle OTIS runs (October 2010 to February 2011)




Scale:

19 (worst) = -10.7%

22 (best) = -2.5%



- Target type and quantity
- Which beams are fired (i.e., laser cleaning)
- Experiment geometry
- Beam location in target chamber

Daily “blowthrough OTIS” measurements are used to monitor debris-shield transmission degradation in a subset of beams




Full OTIS is a 4+ hour operation.
Blowthrough OTIS on a subset
of beams takes <30 min.

Blowthrough OTIS of two witness beam pairs is used to estimate individual transmission of all 60 beams



- Historical correlation of witness beam-pair blowthrough transmission is used to determine the overall system average
- Individual beam transmissions are calculated based on each beam's historical correlation to the system average
- Blowthrough OTIS predicts
 - 60-beam average transmission to ~1%
 - individual beam transmission for beams that are shot to <2% rms*

Examples of blowthrough-estimated individual beam losses compared to actual OTIS measurements



Operations now provides an HED report that *estimates* UV on-target energy as a function of beamline



```

Log Number: 65145          UV On-Target / BWA Degradation Report
23-Feb-2012 19:57:16

Last BWA swap before this shot: 02/05/2012          # target shots since: 101
Reported losses are predicted from witness beam measurements taken on 02/22/2012 # target shots since: 15

Non-SG4 DPPs are not beam specific. Quoted transmissions are average for that DPP type.
    
```

Beam	HED On-Target UV Energy	Estimated BWA Loss	DPP	Estimated DPP Transmission	Adj. On-Target UV Energy
11	502.6	-0.6%	E-SG4-865	98.8%	493.6
13	474.6	-0.9%	SG8	96.6%	454.1
14	500.7	-1.0%	E-SG4-865	98.8%	489.8
18	469.9	-1.6%	SG8	96.6%	446.5
24	483.7	-1.5%	SG8	96.6%	460.2
32	489.6	-0.9%	E-SG4-865	98.8%	479.5
47	477.7	-1.0%	E-SG4-865	98.8%	467.1
59	474.6	-1.1%	SG8	96.6%	453.2
66	472.7	-0.7%	SG8	96.6%	453.4
67	468.6	-1.6%	SG8	96.6%	445.3
68	497.8	-0.9%	E-SG4-865	98.8%	487.4
69	494.3	-1.4%	E-SG4-865	98.8%	481.6
Mean	483.9	-1.1%			467.6
RMS%	2.5	0.3%			3.6
P/V%	7.0	1.0%			10.3

- Estimated DPP transmission is included in this report
 - SG4 DPP transmission is beam specific
 - non-SG4 DPP's are not beam specific; quoted transmission are the average for that DPP type
- This report is included in
 - PI Packet
 - Shot Images and Reports page
 - OMEGA Data Viewer